



① TYPE C JOINT SEALERS SHALL BE HOT POURED SUPER SEAL 444 OR EQUAL.

② FIBER-REINFORCED PORTLAND CEMENT CONCRETE (P.C.C.) SHALL HAVE THE FOLLOWING CHARACTERISTICS: 4000 PSI MIN. COMPRESSIVE STRENGTH @ 28 DAYS, MIN. 6 SACKS OF CEMENT PER CUBIC YARD WITH A MAX. WATER/CEMENT RATIO OF 0.45, AIR ENTRAINMENT 6%  $\pm$  1.5%, SLUMP AT 1 TO 4 INCHES. ALL MATERIALS SHALL CONFORM TO SSPWC SECTION 202. POLYPROPYLENE FIBERS SHALL BE ADDED TO THE P.C.C. PER THE MANUFACTURER'S RECOMMENDATIONS.

NO.	REVISION	DATE	STANDARD DETAILS FOR PUBLIC WORKS CONSTRUCTION	SECTION	RENO
			<div style="text-align: center; font-size: 2em; font-family: cursive;">             BUS PARKING PAD              STRUCTURAL SECTION           </div>	DRAWING NO.	R-118B (312)
				DATE	PAGE
				01/04	142
APPROVED BY :		G.S. 01/04			